

Pump Performance Datasheet

Customer :	Quote number : 792628
Customer reference :	Size : LES 040-125L
Item number : Default	Stages : 1
Service :	Based on curve number : LES 65-40-125L-2-60
Quantity : 1	Date last saved : 29 Sep 2023 2:26 PM

Operating Conditions		Liquid	
Flow, rated	: 30.00 m3/h	Liquid type	: Water
Differential head / pressure, rated (requested)	: 18.50 m	Additional liquid description	:
Differential head / pressure, rated (actual)	: 18.51 m	Solids diameter, max	: 0.0 mm
Suction pressure, rated / max	: 0.00 / 0.00 bar.g	Solids concentration, by volume	: 0.00 %
NPSH available, rated	: Ample	Temperature, max	: 20.00 deg C
Site Supply Frequency	: 50 Hz	Fluid density, rated / max	: 0.999 / 0.999 kg/dm3
Performance		Material	
Speed criteria	: Synchronous	Material selected	: Standard
Speed, rated	: 2875 rpm	Pressure Data	
Impeller diameter, rated	: 124 mm	Maximum working pressure	: 1.93 bar.g
Impeller diameter, maximum	: 139 mm	Maximum allowable working pressure	: 16.00 bar.g
Impeller diameter, minimum	: 110 mm	Maximum allowable suction pressure	: 2.50 bar.g
Efficiency	: 79.86 %	Hydrostatic test pressure	: 24.00 bar.g
NPSH required / margin required	: 4.64 / 0.00 m	Driver & Power Data (@Max density)	
nq (imp. eye flow) / S (imp. eye flow)	: 33 / 67 Metric units	Driver sizing specification	: Rated power
MCSF	: -	Margin over specification	: 0.00 %
Head, maximum, rated diameter	: 19.75 m	Service factor	: 1.00 (used)
Head rise to shutoff	: 6.64 %	Power, hydraulic	: 1.51 kW
Flow, best eff. point	: 36.47 m3/h	Power, rated	: 1.89 kW
Flow ratio, rated / BEP	: 82.25 %	Power, maximum, rated diameter	: 2.25 kW
Diameter ratio (rated / max)	: 89.21 %	Minimum recommended motor rating	: 2.24 kW / 3.00 hp
Head ratio (rated dia / max dia)	: 80.95 %		
Cq/Ch/Ce/Cn [ANSI/HI 9.6.7-2010]	: 1.00 / 1.00 / 1.00 / 1.00		
Selection status	: Acceptable		

Performance based on test acceptance - ISO 9906:2012 3B. Performances are subject to periodic changes due to continuous improvements.

