


## Pump Performance Datasheet

Customer :	Quote number :
Customer reference :	Size : LVI 125-400
Item number : Default	Stages : 1
Service :	Based on curve number : LVI 125-125-400-4-50
Quantity : 1	Date last saved : 16 Nov 2023 6:33 PM


Operating Conditions	Liquid
Flow, rated : 506.9 m3/h	Liquid type : Water
Head, rated (requested) : 208.2 m	Additional liquid description :
Head, rated (actual) : 208.2 m	Solids diameter, max : 0.0 mm
Suction pressure, rated / max : 0.00 / 0.00 bar.g	Solids concentration, by volume : 0.00 %
NPSH available : Ample	Temperature : 20.00 deg C
Site Supply Frequency : 50 Hz	Fluid density : 0.999 / 0.999 kg/dm3
	Viscosity : 1.00 cSt
	Vapor pressure, rated : 0.00 bar.a

Performance	Material
Speed criteria : Synchronous	Material selected : Standard
Speed : 2900 rpm	
Impeller dia. : 414 mm	
Impeller diameter, maximum : 414 mm	
Impeller diameter, minimum : 340 mm	
Efficiency : 73.24 %	
NPSH required / margin required : 11.26 / 0.00 m	
nq (imp. eye flow) / S (imp. eye flow) : 20 / 177 Metric units	
MCSF : -	
Head max. : 235.9 m	
Head rise to shutoff : 13.32 %	
Flow, best eff. point : 506.9 m3/h	
Flow ratio, rated / BEP : 100.00 %	
Diameter ratio (rated / max) : 100.00 %	
Head ratio (rated dia / max dia) : 100.00 %	
Cq/Ch/Ce/Cn [ANSI/HI 9.6.7-2010] : 1.00 / 1.00 / 1.00 / 1.00	
Selection status : Acceptable	



### Pump Performance Curve


Performance based on test acceptance - ISO 9906:2012 3B. Performances are subject to periodic changes due to continuous improvements.



Customer	:	Size	:	LVI 125-400	Flow, rated	:	506.9 m <sup>3</sup> /h
Customer reference	:	Stages	:	1	Head, rated	:	208.2 m
Item number	:	Speed	:	2900 rpm	Fluid density	:	0.999 / 0.999 kg/dm <sup>3</sup>
Service	:	Based on curve number	:	LVI 125-125-400-4-50	Viscosity	:	1.00 cSt
Quantity	:	Efficiency	:	73.24 %	Cq/Ch/Ce/Cn [ANSI/HI 9.6.7-2010]	:	1.00 / 1.00 / 1.00 / 1.00
Quote number	:	Power, rated	:	392 kW			
Date last saved	:	NPSH required	:	11.26 m			

### Multi-Speed Performance Curve

Performance based on test acceptance - ISO 9906:2012 3B. Performances are subject to periodic changes due to continuous improvements.



Customer :	Stages :	Nominal speed :
Customer reference :	Based on curve number :	Flow, rated :
Item number : Default	Efficiency : 73.24 %	Head, rated :
Service :	Power, rated : 392 kW	Speed : 2900 rpm
Quantity : 1	NPSH required : 11.26 m	Impeller dia. : 414 mm
Quote number :	Site Supply Frequency : 50 Hz	Fluid density : 0.999 / 0.999 kg/dm3
Date last saved : 16 Nov 2023 6:33 PM		Viscosity : 1.00 cSt
Size : LVI 125-400		Cq/Ch/Ce/Cn [ANSI/HI 9.6.7-2010] : 1.00 / 1.00 / 1.00 / 1.00

### Life Cycle Cost Datasheet

Customer :	Quantity : 1	Size : LVI 125-400
Customer reference :	Quote number :	Stages : 1
Item number : Default	Date last saved : 16 Nov 2023 6:33 PM	Speed : 2900
Service :		

### Load Profiles and Energy Costs

Expected pump life: 20 years	Load Profile #1	Load Profile #2	Load Profile #3	Load Profile #4	Load Profile #5	Total
Flow: ( m3/h )	15.35	-	-	-	-	-
Operation: ( hours per year )	8,760	-	-	-	-	8,760
Energy cost, present value (\$ per kWh)	0.1	-	-	-	-	-
Speed (rpm)	2900	-	-	-	-	-
Head (m)	235.8	-	-	-	-	-
Efficiency (%)	5.68	-	-	-	-	-
Power, rated (kW)	173	-	-	-	-	-
Motor efficiency (%)	100.00	-	-	-	-	-
Drive/gear efficiency (%)	100.00	-	-	-	-	-
System curve	-	-	-	-	-	-
Energy, total (kWh)	30,364,551.2	-	-	-	-	30,364,551.2
Energy cost, per year	\$ 151,822.76	-	-	-	-	\$ 151,822.76
Energy cost, total present value	\$ 2,277,095.18	-	-	-	-	\$ 2,277,095.18

### Life Cycle Cost Calculation

Additional Annual Costs	Additional One-time Costs, Year 0	Interest and Inflation Rates
Routine maintenance cost : 0.00	Initial investment cost : 0.00	Interest rate, % : 6.00
Repair cost : 0.00	Installation and commissioning cost : 0.00	Inflation rate, % : 3.00
Operating cost : 0.00	Other one-time costs, year 0 : 0.00	<b>Total Net Present Value Costs</b>
Downtime cost : 0.00	<b>Additional One-time Costs, Year 20</b>	Total energy cost : \$ 2,277,095.18
Environmental cost : 0.00	Decommissioning cost : 0.00	Total additional annual cost : \$ 0.00
Other annual costs : 0.00	Other one-time costs, year 20 : 0.00	Total additional one-time cost : \$ 0.00
Total, present value : \$ 0.00	Total, present value : \$ 0.00	Total life cycle cost : \$ 2,277,095.18

**Pump Performance - Additional Data**

Customer	:	Quote number	:
Customer reference	:	Size	: LVI 125-400
Item number	: Default	Stages	: 1
Service	:	Speed	: 2900 rpm
Quantity	: 1	Intellicode	:
		Date last saved	: 16 Nov 2023 6:33 PM

Performance Data		Stage, Speed and Solids Limits	
Head, maximum diameter, rated flow	: 208.2 m	Stages, maximum	: 1
Head, minimum diameter, rated flow	: 112.6 m	Stages, minimum	: 1
Head max.	: 235.9 m	Pump speed limit, maximum	: 3600 rpm
Efficiency adjustment factor, total	: 1.00	Pump speed limit, minimum	: 950 rpm
Power adjustment, total	: 0.00 kW	Curve speed limit, maximum	: 3600 rpm
Head adjustment factor, total	: 1.00	Curve speed limit, minimum	: 950 rpm
Flow adjustment factor, total	: 1.00	Variable speed limit, maximum	: -
Flow adjustment factor, efficiency only (shift BEP)	: 1.00	Variable speed limit, minimum	: -
Flow adjustment factor, end-of-curve only, total	: 1.00	Solids size limit	: 0.0 mm
MCSF adjustment factor	: 1.00	<b>Typical Driver Data</b>	
NPSHR adjustment factor, total	: 1.00	Driver speed, full load	: 2900 rpm
NPSHR slope correction factor	: 1.00	Driver speed, rated load	: 2900 rpm
User applied performance adjustment comments :		Driver efficiency, 100% load	: 100.00 %
NPSH margin dictated by pump supplier	: 0.00 m	Driver efficiency, 75% load	: 100.00 %
NPSH margin dictated by user	: 0.00 m	Driver efficiency, 50% load	: 100.00 %
NPSH margin used (added to 'required' values)	: 0.00 m		

Mechanical Limits	
Torque, rated power, rated speed	: 135 kW/1000 rpm
Torque, maximum power, rated speed	: 159 kW/1000 rpm
Torque, driver power, full load speed	: 0.00 kW/1000 rpm
Torque, driver power, rated speed	: 0.00 kW/1000 rpm
Torque, pump shaft limit	: -
Radial load, worst case	: -
Radial load limit	: -
Impeller peripheral speed, rated	: -
Impeller peripheral speed limit	: -

Various Performance Data	Flow (m3/h)	Head (m)	Efficiency (%)	NPSHr (m)	Power (kW)
Shutoff, rated diameter	0.00	235.9	-	-	168
Shutoff, maximum diameter	0.00	235.9	-	-	168
MCSF	-	-	-	-	-
Rated flow, minimum diameter	506.9	112.6	62.96	-	246
Rated flow, maximum diameter	506.9	208.2	73.24	-	392
BEP flow, rated diameter	506.9	208.2	73.24	11.26	392
120% rated flow, rated diameter	608.2	185.9	71.33	14.35	431
End of curve, rated diameter	728.8	148.0	63.66	21.21	461
End of curve, minimum diameter	648.0	68.76	50.98	16.16	238
End of curve, maximum diameter	728.8	148.0	63.66	21.21	461
Maximum value, rated diameter	-	235.9	73.24	-	461
Maximum value, maximum diameter	-	-	73.24	-	461

System differential pressure	@ Density, rated		@ Density, max	
Differential pressure, rated flow, rated diameter (bar)	20.38		20.38	
Differential pressure, shutoff, rated diameter (bar)	23.10		23.10	
Differential pressure, shutoff, maximum diameter (bar)	23.10		23.10	
Discharge pressure	@ Suction pressure, rated	@ Suction pressure, max	@ Suction pressure, rated	@ Suction pressure, max
Discharge pressure, rated flow, rated diameter (bar.g)	20.38	20.38	20.38	20.38
Discharge pressure, shutoff, rated diameter (bar.g)	23.10	23.10	23.10	23.10
Discharge pressure, shutoff, maximum diameter (bar.g)	23.10	23.10	23.10	23.10

Ratios	
Maximum flow / rated flow, rated diameter	: 143.78 %
Head rated diameter / head minimum diameter, rated flow	: 184.95 %



### Pump Performance - Additional Data

#### Construction

Vertical In-Line Pump Classifications	: Standard	
---------------------------------------	------------	--